

Micromaster MFH200 Specification Sheet

oad Capacity (kg)	400kg
Opening Angle	95°
Production Quality Standard	ISO9001
Adjustment Range	
Height	12mm
Sideways	12mm
Compression	6mm
Adjustment Mechanisms	Turnbuckle Linkage, Set Screws
Adjuster Mechanism Material	AISI 316 Stainless Steel – Self locking
Hinge Weight (Door Mount D01 & Frame Mount F01)	1.2kg
Recycling	Fully Recyclable
Castings / Mouldings	
Material	CD4-MCU Duplex Stainless steel
Process	Lost wax / Investment cast
Treatment	Heat Treated
Finish	Shot Blast Natural
Machined Components	
Material	AISI 316 Stainless Steel
Finish	Electro polished
Emission Rating	Emission Free (Inert)
Corrosion Resistance	Exceeds ISO 9227 & BS EN 1670:1998
Door Installation Types	
Inset	✓
Overlay	✓
Curtain Wall	✓
Curtain Wall Back-To-Back	✓
Door Mounting Options	
Single Point Fixing	✓
Key Slot Mounting	✓
Surface Screw Mounting	✓
Mortised Insert Mounting	-



FOR MORE INFORMATION GO TO www.manfredfrank.com